

TECHNICAL SPECIFICATION

230mm x 3.0mm x 22.23mm
 Phoenix DPC Stone Cutting Disc

PRODUCT DESCRIPTION

Phoenix discs are produced to O.S.A. Safety standards. Manufactured using premium quality materials, Phoenix II discs offer ultimate performance, long life, outstanding value and one of the best cost per-cut ratio's in the market.

FEATURES & BENEFITS

- 6,600 Maximum RPM
- Produced to OSA safety standards
- Suitable for use on Natural Stone, Concrete, Bricks, Roof Tiles
- Exceptional cost per cut ratio

PRODUCT SPECIFICATION

PRODUCT	230mm x 3.0mm x 22.23mm Phoenix DPC Stone Cutting Disc
BRAND	Phoenix
CODE	PH23030DS
FORM	CUT-OFF WHEEL
TYPE	F42
DIMENSIONS	230mm x 3.0mm x 22.23mm
GRADE	C30SBF
OPERATING SPEED	6,600rpm - 80 M/S
REINFORCEMENT	2A

PRODUCT CHARACTERISTICS

CHARACTERISTICS	VALUE	TOLERANCES	CONTROL METHODS
THICKNESS	3.3mm	+/- 0.2mm	Internal Method
WEIGHT	250g	+/- 15g	Internal Method
FACTOR	2	+/- 0.5	Internal Method
DECONSTRUCTION SPEED	Min 12,500rpm	/	EN 12413
UNBALANCE	Max. 3.2g	/	ISO 6103
RUN OUT TOLERANCE	1.0mm	/	ISO 13942

FIRST AID

Eyes (irritant) -

Treat as foreign body in eye. Wash with clean water. If irritation persists seek medical advice.

Skin -

Wash well with soap and water.

Inhalation (non-toxic) -

Classed as nuisance dust, May aggravate respiratory complaints, May cause throat or chest irritation if exposure is high or prolonged, If breathing is difficult move to fresh air and seek medical advice.

Ingestion -

Non-toxic but ingestion should be avoided.

HANDLING & DISPOSAL

Spillage -

Collect up and dispose of in general waste skip.

Disposal -

Landfill tip or as for general factory wastes.

Storage -

Avoid impact damage, particularly to vitrified products. Goods should be stored in suitable storage environment.

Use -

Abrasive wheel regulations apply. Courses available from Abracs Ltd on site or at their HQ.

FIRE/EXPLOSION DATA

Flash Point -

Not Applicable

Extinguishing Media -

Incombustible

Special Procedures -

None required

CONTROL MEASURES

Ventilation -

Good local exhaust ventilation is essential for dry grinding operations. Use a dust mask for nuisance dusts if the dust control is not adequate.

Eye protection -

Good eye protection is essential. Use approved safety goggles.

Gloves -

Use approved safety gloves.

Hygiene -

Good personal hygiene should always be practiced.

Other -

Hearing protection as required.