SIP PROFESSIONAL MIG TRANSFORMER WELDER



This MIG Transformer welder is highly versatile and efficient, due in part to it is 10 position voltage controls and various user-friendly features including; digital displays, 2T/4T trigger modes, creep start, and burnback adjustment.

Item No	05778	
MODEL	SIP HGT4000S MIG TRANSFORMER SEPARATE WIRE FEED	
INPUT SUPPLY	230v	
MIG OUTPUT CURRENT	60 - 300A	
MIG DUTY CYCLE @ 35%	300A	
WELDING VOLT RANGE	17 - 29v	
VOLTAGE CONTROL	10x POSITION SWITCH	
WIRE SIZE	0.8 - 1.2mm	
MAX. WIRE FEED SPEED	24mtr/min	
WEIGHT	120kg	
ADDITIONAL FEATURES	SEPARATE FIRE FEED UNIT 4-ROLL WIRE FEED 2T/4T TRIGGER MODE CREEP START BURNBACK ADJUSTMENT	
EX. VAT	£1699.99	
INC. VAT	£2039.99	





MB36 4mtr WELDING TORCH, 3mtr EARTH LEAD, 5mtr INTERCONNECTING HARNESS

SIP PROFESSIONAL COLUMN SPOT WELDER

SIP CSW25P Pneumatic Column Spot Welder

- · 400v (50A) 1-phase input supply
- 50kVA max / 25kVA @ 50% welding output
- · 5+5mm (mild steel plate) / 20+20mm (bar) welding capacity
- 340 480mm standard arm length
- · 4bar 8bar air pressure
- Single and double spot welding modes; perfect on oxidised or coated steels



foot pedal; for precise workpiece positioning

 Fitted with high quality water cooling hoses







SIP Water Cooler

For use with SIP CSW25P Column Spot Welder

- 400v input supply
- 8ltr/min water flow rate

Item No: 25	125
£849.99	EX.VAT
£1019.99	INC.VAT



2 handheld compact and portable spot welders, fitted with heavy-duty transformers. Manufactured in Italy, and are suitable for automotive and light sheet metal applications, especially where access is limited. Both welders are supplied with quality arms and electrodes.

25287 comes equipped with a manual welding time adjuster

25288 is equipped with an electronic control for welding power, welding time and continuous/pulse functions



item No	20207	20200
MODEL	SIP PROFESSIONAL SPOTWELD 21	SIP PROFESSIONAL SPOTWELD 22E
INPUT SUPPLY	230v (16A)	230v (25A)
MAX. INPUT POWER	1.2kW	2.3kW
MAX. WELDING CURRENT	3800A	6300A
MAX. WELDING CAPACITY	1+1mm (mild steel) / 6+6mm Ø	2+2mm (mild steel) / 6+6mm Ø
OPERATION	Weld timer	Electronic welding current & welding time
ARM / ELECTRODE LENGTH	120mm / 100mm (top), 50mm (bottom)	120mm / 100mm (top), 50mm (bottom)
WEIGHT	10.6kg	11.1kg
ADDITIONAL FEATURES	MANUAL WELDING CURRENT TIME CONTROL FULLY ADJUSTABLE ARM PRESSURE	MICROPROCESSOR CONTROLLED AUTOMATIC WELDING CURRENT TIME CONTROL - DEPENDING ON THICKNESS FULLY ADJUSTABLE TIP PRESSURE
EX. VAT	£779.99	£899.99
INC. VAT	£935.99	£1079.99

